



## MODEL - SSEJ-250T-SG

THREADED ENDS : BSPP/BSPT/NPT

WORKING PRESSURE : 16 bar

WORKING TEMPERATURE : -50°C to +450°C

AXIAL MOVEMENT : +/- 25mm



MODEL - SSEJ-250T-SG  
[SINGLE BELLOW TYPE]

ABOVE PICTURE IS FOR ILLUSTRATION PURPOSE ONLY

SL. NO.	NOMINAL BORE mm	TOTAL LENGTH (L) (+/-5mm)	BELLOWS		AXIAL STIFFNESS N/MM
			CORRS	A	
1	15	350	27	130	99.46
2	20	350	25	130	99.47
3	25	350	25	130	120.32
4	32	350	20	140	122.65
5	40	350	17	140	104.91
6	50	350	16	140	123.11
7	65	350	14	140	129.36
8	80	350	14	140	146.59
9	100	350	12	145	195.99

### CONSTRUCTION

ITEM	PARTS	MATERIAL
1	THREAD ENDS [DN 15-50]	SUS304
1	THREAD ENDS [DN 65-100]	CARBON STEEL
2	BELLOWS	SUS304
3	SEAL RING	SUS304
4	TUBE	CARBON STEEL
5	NUTS	CARBON STEEL
6	TIE ROD	CARBON STEEL
7	INNER SLEEVE	SUS304
8	TIE-ROD HOLDER	CARBON STEEL

OTHER MATERIALS/FINISH AVAILABLE ON REQUEST

### STANDARD FINISH

FLANGES / GUSSETS : GALVO PAINT  
CONTROL ROD : ZINC PLATED  
& HARDWARE

**WARNING** : - Control units must be used to protect this part from excessive movement if piping is not properly anchored.