



**MODEL - SSEJ-250T-SG**  
**THREADED ENDS : BSPP/BSPT/NPT**  
**WORKING PRESSURE : 25 bar**  
**WORKING TEMPERATURE : -50°C to +450°C**  
**AXIAL MOVEMENT : +/- 25mm**



**MODEL - SSEJ-250T-SG**  
**[SINGLE BELLOW TYPE]**  
 ABOVE PICTURE IS FOR ILLUSTRATION PURPOSE ONLY

SL. NO.	NOMINAL BORE	TOTAL LENGTH (L)	BELLOWS		AXIAL STIFFNESS
			CORRS	A	
	mm	(+/-5mm)			N/MM
1	15	350	27	130	185.53
2	20	350	25	130	210.00
3	25	350	25	130	219.43
4	32	350	20	140	228.77
5	40	350	17	140	214.75
6	50	350	16	140	226.17
7	65	350	14	140	243.11
8	80	350	14	140	278.39
9	100	350	12	145	296.77

■ CONSTRUCTION		
ITEM	PARTS	MATERIAL
1	THREAD ENDS [DN 15-50]	SUS304
1	THREAD ENDS [DN 65-100]	CARBON STEEL
2	BELLOWS	SUS304
3	SEAL RING	SUS304
4	TUBE	CARBON STEEL
5	NUTS	CARBON STEEL
6	TIE ROD	CARBON STEEL
7	INNER SLEEVE	SUS304
8	TIE-ROD HOLDER	CARBON STEEL

OTHER MATERIALS/FINISH AVAILABLE ON REQUEST

**STANDARD FINISH**  
 FLANGES / GUSSETS : GALVO PAINT  
 CONTROL ROD : ZINC PLATED  
 & HARDWARE

**WARNING :** - Control units must be used to protect this part from excessive movement if piping is not properly anchored.