



**MODEL - SSEJ-250W-SG**  
**WELDED ENDS : SCHEDULE 40 PIPE**  
**WORKING PRESSURE : 16 / 25 bar**  
**WORKING TEMPERATURE : -50°C to +450°C**  
**AXIAL MOVEMENT : +/- 25mm**



**MODEL - SSEJ-250T-SG**  
**[SINGLE BELLOW TYPE]**  
ABOVE PICTURE IS FOR ILLUSTRATION PURPOSE ONLY

SL. NO.	NOMINAL BORE	TOTAL LENGTH (L)	BELLOWS	
			CORRS	A
1	15	350	27	130
2	20	350	25	130
3	25	350	25	130
4	32	350	20	140
5	40	350	17	140
6	50	350	16	180
7	65	350	14	140
8	80	350	14	140
9	100	350	12	145
10	125	400	12	145
11	150	400	10	145
12	200	400	8	150
13	250	400	8	150
14	300	400	8	150
15	350	400	6	140
16	400	400	6	140
17	450	400	6	155
18	500	400	6	170
19	600	400	4	150
20	650	500	4	150
21	700	500	3	150
22	750	500	3	150
23	800	500	3	150
24	900	500	3	150
25	1000	500	3	150

■ CONSTRUCTION		
ITEM	PARTS	MATERIAL
1	TUBE ENDS	CARBON STEEL
2	BELLOWS	SUS304
3	SEAL RING	SUS304
4	TUBE	CARBON STEEL
5	NUTS	CARBON STEEL
6	TIE ROD	CARBON STEEL
7	INNER SLEEVE	SUS304
8	TIE-ROD HOLDER	CARBON STEEL

OTHER MATERIALS/FINISH AVAILABLE ON REQUEST

STANDARD FINISH  
 FLANGES / GUSSETS : GALVO PAINT  
 CONTROL ROD : ZINC PLATED  
 & HARDWARE

**WARNING :** - Control units must be used to protect this part from excessive movement if piping is not properly anchored.