



Model -SSBH -150F

FLANGED ENDS - ANSI ASA 150 OR BS4504 PN16

WORKING TEMPERATURE : -50°C to +450°C

WARNING : - Control units must be used to protect this part from excessive movement if piping is not properly anchored.

S.NO.	NOMINAL BORE mm	TOTAL LENGTH (L) (+ / - 5mm)	OFFSET (+ / -mm)	WORKING PRESSURE
1.	15	250	20	20
2.	20	250	20	20
3.	25	250	20	20
4.	32	250	20	20
5.	40	250	16	20
6.	50	250	16	20
7.	65	250	16	16
8.	80	250	16	16
9.	100	250/360*	15/25	16
10.	125	300	15	16
11.	150	300/380	12/25	16
12.	200	300	8	16
13.	250	350	8	16
14.	300	350	7	16
15.	350	350	7	16
16.	400	350	5	16
17.	500	350	5	16
18.	600	350	5	16
19.	650	550	5	16

■ CONSTRUCTION

ITEM	PARTS	MATERIAL
1	BELLOWS	SST304
2	BRAID	SST304
3	FLANGE	CARBON STEEL
4	STANDARD FITTINGS FINISH	GALVO PAINT

OTHER MATERIALS /FINISH AVAILABLE ON REQUEST