



S.NO.	NOMINAL	TOTAL	BELLOWS (ANSI 300#)	
	BORE		LENGTH	CORRS
1.	40 mm	160 (+/-5mm)	25 BAR	2
2.	50	160	15	2
3.	65	160	13	2
4.	80	160	11	2
5.	100	170	10	2
6.	125	180	9	2
7.	150	180	9	2
8.	200	230	9	2
9.	250	240	8	2
10.	300	240	8	2
11.	350	270	8	2
12.	400	270	8	2
13.	450	280	6	3
14.	500	280	6	3
15.	600	300	6	3

■ CONSTRUCTION

ITEM	PARTS	MATERIAL
1	BELLOWS	SST304
2	TIE RODS	CARBON STEEL
3	FLANGE	CARBON STEEL
4	GUSSET	CARBON STEEL

■ STANDARD FINISH

1	FLANGES/GUSSETS	: GALVO PAINT
2	CONTROL RODS & HARDWARE	: ZINC PLATED

OTHER MATERIAL S/FINISHES ON REQUEST

Model - SSEJ-500H-SG - WITH OPTIONAL TIE RODS
FLANGED ENDS - ANSI ASA 300
WORKING PRESSURE : 25 bar
WORKING TEMPERATURE : -50°C to +450°C
AXIAL & LATERAL MOVEMENT : + / -10mm

WARNING : - Control units must be used to protect this part from excessive movement if piping is not properly anchored.