



## Model -SSBH -300F

FLANGED ENDS - ANSI ASA 300 OR BS4504 PN25

WORKING TEMPERATURE : -50°C to +450°C

**WARNING :** - Control units must be used to protect this part from excessive movement if piping is not properly anchored.

S.NO.	NOMINAL BORE mm	TOTAL LENGTH (L) (+ / -5mm )	OFFSET (+ / -mm)	WORKING PRESSURE
1.	15	300	20	25
2.	20	300	20	25
3.	25	300	20	25
4.	32	300	20	25
5.	40	300	16	25
6.	50	300	16	25
7.	65	300	16	25
8.	80	300	16	25
9.	100	300	15	25
10.	125	350	15	25
11.	150	350	12	25
12.	200	350/550	8 /25	25
13.	250	400	8	25
14.	300	400	7	25
15.	350	400	7	25
16.	400	400	5	25
17.	500	400	5	25
18.	600	400	5	25
19.	650	-	-	-

### ■ CONSTRUCTION

ITEM	PARTS	MATERIAL
1	BELLOWS	SST304
2	BRAID	SST304
3	FLANGE	CARBON STEEL
4	STANDARD FITTINGS FINISH	GALVO PAINT

OTHER MATERIALS /FINISH AVAILABLE ON REQUEST