



MODEL - SDJ-150F/300F

FLANGED ENDS - BS4504 PN10 / PN16 / PN25
 WORKING PRESSURE : 10 bar / 16 bar / 25 bar
 DFDF DSFS

PARTS		
1	FLANGE	CARBON STEEL
2	STUD / NUT	STEEL WITH ZINC PLATED
3	RUBBER GASKET	EPDM
4	GLAND	CARBON STEEL
5	ADAPTOR	CARBON STEEL

DN	L	SDJ-150F PN 10			SDJ-150F PN 16			SDJ-300F PN 25		
		D	K	n-d0	D	K	n-d0	D	K	n-d0
65	200	185	145	4-Ø18	185	145	4-Ø18	185	145	8-Ø18
80	200	200	160	8-Ø18	200	160	8-Ø18	200	160	8-Ø18
100	200	220	180	8-Ø18	220	180	8-Ø18	235	190	8-Ø22
125	200	250	210	8-Ø18	250	210	8-Ø18	270	220	8-Ø26
150	200	285	240	8-Ø22	285	240	8-Ø22	300	250	8-Ø26
200	220	340	295	8-Ø22	340	295	12-Ø22	360	310	12-Ø26
250	230	395	350	12-Ø22	405	355	12-Ø26	425	370	12-Ø30
300	250	445	400	12-Ø22	460	410	12-Ø26	485	430	16-Ø30
350	260	505	460	16-Ø22	520	470	16-Ø26	555	490	16-Ø33
400	270	565	515	16-Ø26	580	525	16-Ø30	620	550	16-Ø36
450	270	615	565	20-Ø26	640	585	20-Ø30	670	600	20-Ø36
500	280	670	620	20-Ø26	715	650	20-Ø33	730	660	20-Ø36
600	300	780	725	20-Ø30	840	770	20-Ø36	845	770	20-Ø39
700	300	895	840	24-Ø30	910	840	24-Ø36	960	875	24-Ø42
800	320	1015	950	24-Ø33	1025	950	24-Ø39	1085	990	24-Ø48
900	320	1115	1050	28-Ø33	1125	1050	28-Ø38			
1000	340	1230	1160	28-Ø36	1255	1170	28-Ø42			
1200	360	1455	1380	32-Ø39	1485	1390	32-Ø48			

WARNING : - Control units must be used to protect this part from excessive movement if piping is not properly anchored.