



MODEL - SSEJ-150F-SG
FLANGED ENDS - ANSI ASA 150 OR BS4504 PN 16
 WORKING PRESSURE : 16 bar
 WORKING TEMPERATURE : -50°C to +450°C
 AXIAL MOVEMENT : + / -100mm

STANDARD FINISH
 FLANGES / GUSSETS : GALVO PAINT
 CONTROL ROD : ZINC PLATED
 & HARDWARE

WARNING : - Control units must be used to protect this part from excessive movement if piping is not properly anchored.

SL. NO.	NOMINAL BORE	TOTAL LENGTH (L) (+/-5mm)	BELLOWS	
1	20	880	28+28+28	185
2	25	880	28+28+28	185
3	32	920	28+28+28	200
4	40	920	26+26+26	200
5	50	920	26+26+26	200
6	65	1000	16+16+16	192
7	80	1000	16+16+16	192
8	100	1010	14+14+14	196
9	125	1010	14+14+14	196
10	150	1010	14+14+14	196
11	200	1000	12+12+12	192
12	250	1000	12+12+12	192
13	300	1000	12+12+12	192
14	350	1050	8+8+8	210
15	400	1050	8+8+8	210
16	450	1050	8+8+8	210
17	500	1050	8+8+8	210
18	600	1050	6+6+6	210

CONSTRUCTION

ITEM	PARTS	MATERIAL
1	BELLOWS	SST304 (2 PLY)
2	TUBE	CARBON STEEL
3	GUSSET	CARBON STEEL
4	TIE RODS	CARBON STEEL
5	INNER SLEEVE	SST304
6	FLANGE	CARBON STEEL

OTHER MATERIALS/FINISH AVAILABLE ON REQUEST