



S.NO.	NOMINAL	TOTAL LENGTH (+/-5mm)	BELLOWS (PN40)	
	BORE mm		CORRS	PLY
1.	40	150	16	3
2.	50	150	16	3
3.	65	150	12	3
4.	80	150	11	3
5.	100	150	10	3
6.	125	150	10	3
7.	150	150	10	3
8.	200	200	10	3
9.	250	200	10	3
10.	300	200	10	3
11.	350	230	7	3
12.	400	230	7	3
13.	450	230	7	3
14.	500	230	6	3
15.	600	230	6	3

■ CONSTRUCTION

ITEM	PARTS	MATERIAL
1	BELLOWS	SST304
2	TIE RODS	CARBON STEEL
3	FLANGE	CARBON STEEL
4	GUSSET	CARBON STEEL

■ STANDARD FINISH

1	FLANGES/GUSSETS	: GALVO PAINT
2	CONTROL RODS & HARDWARE	: ZINC PLATED

OTHER MATERIALS/FINISH ON REQUEST

Model - SSEJ-500H-SG - WITH TIE RODS
FLANGED ENDS - BS4504 PN40

WORKING PRESSURE : 40 bar
WORKING TEMPERATURE : -50°C - 450°C
AXIAL & LATERAL MOVEMENT : + / -10mm

WARNING : - Control units must be used to protect this part from excessive movement if piping is not properly anchored.