

# 1.070 SONODEC<sup>®</sup> ACOUSTICALLY INSULATED DUCTING

The **SONODEC<sup>®</sup>** series consists of a perforated aluminum laminate inner duct, a polyester barrier to prevent the diffusion of glass wool particles, thermally and acoustically insulated with a glass wool layer and provided with an Aluminium laminated outer jacket



## Applications in practice

- Air-conditioning systems
- Air supply systems
- Preventing condensation in air ventilation systems
- Decreasing of machine noises
- Consult the selection tables

	SONODEC <sup>®</sup> 25	SONODEC <sup>®</sup> 250	SONODEC <sup>®</sup> CE
<b>Mechanical properties</b>			
Temperature range (°C) inner duct	-30 - +140	-30 - +250	-30 - +250
outer duct	-30 - +140	-30 - +140	-30 - +140
Maximum operating pressure (Pa)	+2500	+2500	+2500
Maximum air velocity (m/s)	30	30	30
Diameter range (mm)	76 - 508	65 - 635	102 - 508
<b>Fire classes according to</b>			
The Netherlands (NEN 6065/6066)	1	1	x
Germany (DIN 4102)	B2	B1	x
France (CSTB)	M1	M0/M1	M0/M1
Switzerland (BKZ)	x	5.2	x
United Kingdom (BS 476)	6, 7 and 20	6, 7 and 20	x
Austria (B3800)	B1	B1	x
Italy (CSI)	1-0	1-0	x
<b>Technical data</b>			
Article code	DS{Ø}/Length	DSX{Ø}/Length	DSXCE{Ø}/Length
Material structure / Construction	see product specific properties		
Wire spacing inner duct -upto Ø 102	25 mm	25 mm	-
- Ø 102 and larger	36 mm	18 <sup>1)</sup> mm	36 mm
Minimal bending radius	0.54 x Ø + †	0.58 x Ø + †	0.54 x Ø + †
Standard length (meters)	10	10	10
Standard color	aluminium	aluminium	aluminium

x = not been tested - † = thickness of the glass wool - <sup>1)</sup> = two different wires have been used alternately

## Product specific properties

The **SONODEC<sup>®</sup>** is also available, on request, with a 50 mm glass wool layer, the article number is: DS(x)50{Ø}

- Material structure: - perforated aluminum laminate / barrier / glass wool / aluminum laminate
- Construction: - inner duct :aluminum, polyester laminate
- barrier :closed polyester film (*Sonodec CE no barrier*)
- glass wool blanket :25 (or 50) mm, 16 kg/m<sup>3</sup>
- outer jacket :aluminum, polyester laminate
- R-value glass wool :0.69 (25 mm) or 1.4 (50 mm) m<sup>2</sup>K/W (ASTM C177-76)

The **SONODEC<sup>®</sup>** fulfills all the requirements and are classified as specified within:

**EN 13180** :“Ventilation for buildings-Ductwork- Dimensions and mechanical requirements for flexible ducts”

## Restrictions in the range of applications

The **SONODEC<sup>®</sup>** ducts are not suitable for transporting air with a high concentration of acid and base. Neither are the **SONODEC<sup>®</sup>** ducts suitable for discharging combustion gases.

## PLEASE NOTICE:

The consultant is responsible for the actual installation and mounting of the product.

The mentioned values with respect to temperatures are not appropriate to be used to determine the physical properties.

These properties are also dependent on humidity and the temperature of the air inside and outside of the H.V.A.C. system.

The information contained in this brochure was current on the publication date. The Company reserves the right to make changes in details at any time without prior notice. In order to avoid misunderstandings, any interested party is advised to contact the Company checking for any changes in materials and/or information after this brochure was published.

Version 2011

DEC International<sup>®</sup> P.O.Box35, NL-7500AA, Enschede, The Netherlands, [www.decinternational.com](http://www.decinternational.com)

# 1.070 SONODEC<sup>®</sup> ACOUSTICALLY INSULATED DUCTING

## SONODEC<sup>®</sup> 25 Sound attenuation

SONODEC <sup>®</sup> 25		(Test report nr. AB323-1 Peutz bv - The Netherlands)					
D <sub>n</sub> (mm)	L (mtr)	Attenuation, dB - Mid-frequency, Hz					
		125	250	500	1000	2000	4000
082	1	16	26	33	38	28	17
	2	21	37	48	53	46	29
	3	29	45	49	54	57	38
102	1	9	19	32	37	31	21
	2	19	33	52	53	49	36
	3	25	39	50	52	54	40
127	1	12	20	21	25	29	17
	2	17	31	44	45	46	26
	3	23	46	44	47	51	34
160	1	17	22	22	27	19	14
	2	31	39	34	38	31	20
	3	29	43	41	46	39	27
203	1	7	15	17	20	16	13
	2	20	34	32	35	30	22
	3	18	40	38	41	39	30
254	1	16	16	16	16	13	10
	2	26	31	28	33	25	18
	3	32	36	32	37	34	27
315	1	11	12	12	14	11	7
	2	28	25	22	27	22	15
	3	27	32	28	34	28	19
457	1	12	10	8	8	6	8
	2	20	17	15	16	13	12
	3	25	22	21	25	19	16
508	1	8	8	8	9	6	7
	2	20	17	16	17	11	11
	3	24	22	20	25	15	14

## SONODEC<sup>®</sup> 250 Sound attenuation

SONODEC <sup>®</sup> 250		(Test report nr. AB323-2 Peutz bv - The Netherlands)					
D <sub>n</sub> (mm)	L (mtr)	Attenuation, dB - Mid-frequency, Hz					
		125	250	500	1000	2000	4000
082	1	16	25	34	38	30	20
	2	22	37	48	54	46	30
	3	30	43	41	43	55	43
102	1	11	25	31	36	23	15
	2	17	31	51	50	38	26
	3	20	44	51	52	51	33
127	1	11	19	23	27	25	19
	2	17	31	43	43	35	22
	3	21	40	45	48	47	27
160	1	15	26	22	27	18	13
	2	22	38	35	39	29	20
	3	33	43	39	43	39	27
203	1	6	13	15	18	11	10
	2	15	31	32	38	21	18
	3	16	36	40	42	28	24
254	1	9	11	12	10	7	11
	2	21	24	24	22	13	15
	3	29	33	31	30	19	24
315	1	8	8	8	7	6	8
	2	16	15	14	13	9	13
	3	23	23	21	19	12	17
457	1	8	8	6	6	5	7
	2	18	15	14	12	8	10
	3	24	21	20	18	11	15
508	1	7	8	7	7	6	7
	2	-	-	-	-	-	-
	3	-	-	-	-	-	-

The information contained in this brochure was current on the publication date. The Company reserves the right to make changes in details at any time without prior notice. In order to avoid misunderstandings, any interested party is advised to contact the Company checking for any changes in materials and/or information after this brochure was published.

Version 2011

DEC International<sup>®</sup> P.O.Box35, NL-7500AA, Enschede, The Netherlands, [www.decinternational.com](http://www.decinternational.com)