



Model -SSBH -150F / 300F

FLANGED ENDS - ANSI ASA 150 / 300 OR BS4504 PN16 / PN25
 WORKING TEMPERATURE : -50°C to +450°C

S.NO.	NOMINAL BORE mm	TOTAL LENGTH (L) (+ / - 5mm)		OFFSET (+ / -mm)	WORKING PRESSURE	
		150F	300F		150F	300F
1.	15	250	300	20	20	25
2.	20	250	300	20	20	25
3.	25	250	300	20	20	25
4.	32	250	300	20	20	25
5.	40	250	300	16	20	25
6.	50	250	300	16	20	25
7.	65	250	300	16	16	25
8.	80	250	300	16	16	25
9.	100	250	300	15	16	25
10.	125	300	350	15	16	25
11.	150	300	350	12	16	25
12.	200	300	350	8	16	25
13.	250	350	400	8	16	25
14.	300	350	400	7	16	25
15.	350	350	400	7	16	25
16.	400	350	400	5	16	25
17.	500	350	400	5	16	25
18.	600	350	400	5	16	25
19.	650	550	-	5	16	-

■ CONSTRUCTION

ITEM	PARTS	MATERIAL
1	BELLOWS	SST304
2	BRAID	SST304
3	FLANGE	CARBON STEEL
4	STANDARD FITTINGS FINISH	GALVO PAINT

OTHER MATERIALS /FINISH AVAILABLE ON REQUEST