



Design Conditions		
Working Temperature	20	°C

Note:
End fittings can be supplied in the form of flanges, screwed connectors or tube ends

DN	L	Working Pressure	Test Pressure	Max. Bend Radius Dynamic	Type No.
mm	mm	bar	bar	mm	
6	300	167	251	110	T-FLEX 6
8	300	136	204	130	T-FLEX 8
10	300	100	150	150	T-FLEX 10
12	300	74	111	165	T-FLEX 12
16	300	70	105	195	T-FLEX 16
20	300	65	98	200	T-FLEX 20
25	300	50	75	200	T-FLEX 25
32	300	39	59	250	T-FLEX 32
40	300	35	53	250	T-FLEX 40
50	300	30	45	350	T-FLEX 50
65	300	26	39	410	T-FLEX 65
80	300	22	33	450	T-FLEX 80
100	300	21.5	32	560	T-FLEX 100
125	500	11.5	17	711	T-FLEX 125
150	500	11.2	17	864	T-FLEX 150
200	500	7	11	1067	T-FLEX 200
250	500	9.6	14	1753	T-FLEX 250
300	500	12.07	18	1880	T-FLEX 300

3	End Fitting	2	CARBON OR STAINLESS STEEL	
2	Braid	1	S/S TYPE 304 OR 316	
1	Hose	1	S/S TYPE 321	
NO.	PART NAME	QTY	MATERIAL	REMARK



Engineered Solutions Ltd.

Unit 1, Heol Cropin, Dafen Park, Llanelli
SA14 8QW Wales UK
Tel: +44(0)1554 744500
Fax: +44(0)1554 746435

Single Braided Hose

T-FLEX